

T82XW

NEW **COMING SOON**



Touchscreen 8000 Series stainless steel indicator with customizable applications

- Multiplied communication interfaces including optional Bluetooth and wi-fi
- Unique applications including SQC and Vehicle Weighing
- Ability to support up to 16x350ohm load cells



Application

Accumulation and Formula weighing, Parts Counting, Weighbridges, SQC, Vehicle, Price Computing and Industrial Labelling, Single-Product Dosage Systems, Multi-component Dosage Systems

Display

Backlit graphic display with touch screen technology

Operation

AC Power

Communication

2*RS232, RS485 and optional: RS232/RS485, USB, Ethernet

Construction

IP68 4X stainless steel housing and mounting bracket

Design Features

Check weighing lights with selectable operation and audible signal settings, multi operating languages, QWERTY, AZERTY, QWERTZ keyboard options integrated in the touch screen, real-time clock, integrated alibi memory, built-in micro SD slot for recording configuration, logos and customized screens, 4 independent analog channels, selectable environmental and auto-print settings, stability indicator, overload/underload indicators



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

Model	Item N°	Price £
T82XW – GB	30325753	840

Accessories	Item N°	Price £
I/O Input, Set(2), T82XW	30325822	23
I/O Output, Set(4), T82XW	30325823	45
Analog output Board, T82XW	30344022	132
6 In /12 Out I/O Board, T82XW	30344023	159
Multi L/C Input, 4 channel, T82XW	30331635	23
Build-in USB flash driver, T82XW	30331636	177
RS232-USB, T82XW	30331637	77
Build-in optoisolated RS485, T82XW	30331643	63
Wall mount Kit, T82XW	30331644	68
In_Use_Cover Kit, T82XW	30328139	77
License for Display tool, T82XW	30344025	181
Serial to mini DIN connector, T82XW	30344026	63
RS232/C serial cable 1.5m, T82XW	30344027	63
Ethernet cable 1.5m, T82XW	30344028	72

Terminal is delivered with "accumulation and formula weighing" application software installed. Other software applications are available on <http://dmx.Ohaus.Com> for free.

CKW55

Checkweighing indicator with IP66 protection

- Multiple configurations
- Optional Internal rechargeable battery
- Food safety certification (NSF) and supports an HACCP compliant quality system

Application Weighing (6 units), checkweighing, negative checkweighing, auto tare, totalisation, basic statistics

Display LED, user configurable, 24 segment traffic light LED Bar Graph

Operation Internal universal power supply or optional internal NiMH rechargeable battery


Communication RS232 interface, optional RS422/485 and optional AC/DC relay outputs

Construction IP66 Stainless steel housing

Design Features Support an HACCP compliant quality system, NSF certified, 20 part library, 7 500 d and up to 3000 e



Model	Item N°	Price £	Accessories	Item N°	Price £
CKW55	80251030	565			
Accessories	Item N°	Price £	Accessories	Item N°	Price £
Wall Mount Bracket for CKW55	71167964	37	Relay kit AC for CKW	71167967	229
RS422/485 Interface kit for CKW	71167965	96	Relay kit DC for CKW	71173377	193
Internal rechargeable battery kit CKW	71167966	176	Foot switch	71173378	30
Column Kit S/Steel, 68 cm for CKW-55	80251059	77	Column SS 230mm CKW for platforms/CKW55	71167972	68



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

T72XW

Advanced performance stainless steel indicator with external device control capabilities

- 50,000 displayed resolution and the ability to support up to 10 load cells
- Two available option slots enable a wide range of connectivity interfaces
- Vivid graphic display with on-screen prompts and an alphanumeric keypad with designated keys for common functions such as Tare and ID information

Application Weighing, Parts Counting, Check Weighing, Animal / Dynamic Weighing

Display Transflective graphic LCD with white backlight, 240 x 96 pixels

Operation AC Power (Included)

Communication Easy access communication port including RS232 (included), Ethernet and 2nd RS232 or RS485 (accessories sold separately). GLP/GMP data output with real-time clock

Construction IP66/NEMA 4X stainless steel housing and mounting bracket


Design Features Check weighing lights with selectable operation and audible signal settings, sealed front panel, five operating languages (English, Spanish, French, German and Italian), selectable environmental and auto-print settings, stability indicator, overload/underload indicators



OPTION



Model	Item N°	Price £	Accessories	Item N°	Price £
T72XW-GB	30126958	579			
Accessories	Item N°	Price £	Accessories	Item N°	Price £
Ethernet Kit, T72XW	30132163	64			
USB with I/O kit, T72XW	30132164	64			
COM2 Kit, T72XW	30132165	75			
Column Kit, 350mm, SST	80500725	50			
Column Kit, 680mm, SST	80500726	60			



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

T71P

Multifunctional 7000 Series ABS indicator for advanced applications



- Advanced applications including accumulation, library and optional alibi memory
- Two scale operation plus multiple interface and relay options
- User-selectable language settings & user configurable resolution up to 50 000 d

Application Weighing (6 units + custom unit), display hold, dynamic weighing, counting, checkweighing, percentage weighing, auto-tare, accumulation, library of up to 256 records, optional alibi memory

Display LCD display with white LED backlight, alphanumeric line and multi-language, plus 3 colour checkweigh LED

Operation Internal universal power supply, 6 x C batteries or optional internal NiMH rechargeable battery

Communication RS232 Interface with GMP, Time-Date; optional RS422/485, AC/DC Relay, 2nd RS232

Construction ABS housing

Design Features Alphanumeric keypad, reversible rear cover for cable exit above or below the indicator housing, simple plug and play installation of options, 50 000 d and up to 10 000 e



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

Model	Item N°	Price £
T71P	72200261	529

Accessories	Item N°	Price £
Foot switch	71173378	30
Wall Mount Kit	72200227	23
Alibi Memory Option Kit	80500503	32
AC Relay Option Kit	80500720	152
Base Mount Kit	80500722	23
Column Kit, 35 cm (painted)	80500723	29
Column kit, 68 cm paint Def.platform	80500724	33
DC Relay Kit	80500727	132
Battery (Rechargeable Kit)	80500729	81
RS422/485 (Interface Kit)	80500731	38
RS232 (Interface Kit)	80500733	24
Load Cell Cable Adapter Kit	80500736	25
RS232-USB (Interface Kit)	30304101	46
RS232-Ethernet (Interface Kit)	30304102	68

T51XW




OPTION

Multifunctional 5000 Series washdown indicator

- IP66 stainless steel housing
- Multiple interface and relay options
- High resolution, user configurable up to 30 000 d

Application	Weighing (6 units + custom unit), display hold, dynamic weighing, counting, checkweighing, percentage weighing, auto-tare
Display	LCD display with white LED backlight plus 3 colour checkweigh LED
Operation	Internal universal power supply or optional internal NiMH rechargeable battery
Communication	RS232 Interface with GMP, Time-Date, optional RS422/485, AC/DC Relay, 2nd RS232
Construction	IP66 Stainless steel housing
Design Features	Hinged front cover for easy servicing, simple plug and play installation of options, 30 000 d and up to 10 000 e



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

Model	Item N°	Price £
T51XW-GB	80251805	469

T51P



OPTION

Multifunctional 5000 Series ABS indicator

- Advanced applications including dynamic and checkweighing
- Multiple interface and relay options
- High resolution, user configurable up to 30 000 d

Application	Weighing (6 units + custom unit), display hold, dynamic weighing, counting, checkweighing, percentage weighing, auto-tare
Display	LCD display with white LED backlight plus 3 colour checkweigh LED
Operation	Internal universal power supply, 6 x C batteries or optional internal NiMH rechargeable battery
Communication	Optional RS422/485, AC/DC Relay,
Construction	ABS housing
Design Features	Reversible rear cover for cable exit above or below the indicator housing, non-slip rubber feet. Simple plug and play installation of options, 30 000 d and up to 10 000 e



Model	Item N°	Price £
T51P	72200198	329

Accessories	T51XW	T51P	Item N°	Price £
Foot switch	•	•	71173378	30
AC Relay Option Kit	•	•	80500720	152
Column kit, 35 cm S/S Def. pf	•		80500725	50
Column kit, 68 cm S/S Def. pf	•		80500726	60
DC Relay Kit	•	•	80500727	132
Battery (Rechargeable Kit)	•	•	80500729	81
RS422/485 (Interface Kit)	•	•	80500731	38
RS232 (Interface Kit)	•	•	80500733	24
Mounting kit wall	•		80500735	29
Kit console murale		•	72200227	23
Base Mount Kit		•	80500722	23
Column Kit, 35 cm (painted)		•	80500723	29
Column kit, 68 cm paint Def. platform		•	80500724	33
Load Cell Cable Adapter Kit		•	80500736	25
Load Cell Cable – Sealing Collar		•	80500737	3
RS232-USB (Interface Kit)	•	•	30304101	46
RS232-Ethernet (Interface Kit)	•	•	30304102	68



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

T32XW



3000 Series stainless steel indicator for washdown environments

- IP65 stainless steel with hinged front cover for easy servicing
- Intuitive usage
- Internal rechargeable battery

Application	Weighing (5 units), basic parts counting
Display	LCD with white LED backlight
Operation	Internal universal power supply or internal rechargeable battery
Communication	RS232 Interface
Construction	IP65 Stainless steel housing
Design Features	Hinged front cover for easy servicing, 20 000 d and up to 6 000 e



Model	Item N°	Price £
T32XW-GB	80252916	249
Accessories	Item N°	Price £
Column kit 35 cm S/S Def. platform/T3xXW	80251745	46
Column kit 70 cm S/S Def. platform/T3xXW	80251746	55
Mounting kit wall SS T32XW	80251748	27



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

T32M



Sturdy 3000 Series metal indicators

- Feature-rich, yet simple to use and easy to learn
- Intuitive usage
- Two display versions

Application	Weighing (5 units), basic parts counting, weight accumulation
Display	T32MC with backlit LCD / T32ME with LED
Operation	AC adaptor (included)
Communication	RS232 Interface
Construction	ABS front panel with painted carbon steel rear housing
Design Features	Textured-surface paint minimizes scratches, 20 000 d and up to 6 000 e



Model	Item N°	Price £
T32ME	83997627	155
T32MC	83997628	159



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

Accessories available for all Defender platforms and Defender terminals

Model	Item N°	Price £
RS232-USB (Interface Kit)	30304101	46
RS232-Ethernet (Interface Kit)	30304102	68

T31P



3000 Series basic industrial indicator

- Reversible rear cover for cable exit above or below the indicator housing
- Intuitive usage
- Internal rechargeable battery

Application	Weighing (5 units), basic parts counting
Display	LCD with white LED backlight
Operation	AC adaptor (supplied) with internal rechargeable battery
Communication	RS232 Interface
Construction	ABS housing
Design Features	Integrated key-hole mounts on back cover, 20 000 d and up to 6 000 e



Model	Item N°	Price £
T31P	83998243	165



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67


Accessories	Item N°	Price £
Column kit 35 cm paint. Def. platform/T31P	80251743	29
Column kit 70 cm paint. Def. platform/T31P	80251744	38
Wall Mount Kit, painted steel T31P	80251747	16

T24PE

Dependable and durable 2000 Series indicator at affordable price

- Easy-to-read Red LED display
- Optional RS232C with manual/continuous/interval printing
- Versatile power capabilities including AC adaptor and rechargeable battery in standard

Application	Weighing (3 units), parts counting, accumulation
Display	6-digit, 7-segment red LED
Operation	AC adapter with internal rechargeable lead acid battery
Communication	Optional RS232
Construction	ABS plastic housing
Design features	Hardware configuration lockout switch, software included for parts counting mode with selectable sample sizes, selectable span calibration points



OPTION



FOR PRINTERS, CABLES AND SOFTWARE
SEE P. 65-67

Model	Item N°	Price £
T24PE	30235894	109

Accessories	Item N°	Price £
RS232 Kit	30101019	15
Folding Column Kit	30101016	22
In-Use-Cover	30101017	10
Load Cell Cable Adapter Kit	30101021	10
SF40A Impact Printer	30064202	373